

KHM 500

SINGLE STAGE, CENTRIFUGAL, SINGLE SUCTION IMPELLER, MIDSHIP MOUNTED



DIMENSIONS & WEIGHT

- 36" L x Body Width x 48" H, 650 lbs. (295 kg)

APPLICATIONS

- Mini Pumper, pumper tanker, wildland/attack fire

STANDARD FEATURES

ASSEMBLY #1

- 1 - 3" NPTF outlet
- 1 - 4" NPTF inlet
- Companion flanges

ASSEMBLY #2

- 3 - 4" NPTF inlet
- 1 - 4" tank to pump suction opening
- 2 - 2½" NPT discharge openings
- Discharge head check valve
- Suction elbow and tee

ASSEMBLY #3

- 2 - 2½" NH ¼ turn, ball, self-locking valves and caps
- 2 - 4" NH suction adapters and caps
- 2 - 2½" NPT suction openings
- 1 - 4" tank to pump suction opening
- 2 - 2½" NPT discharge openings
- Body width: 70" - 72"
- Complete

OPTIONS

- Available as a KHMH high pressure pump with pressures up to 600 psi

PERFORMANCE

500 gpm (1893 L/M) @ 150 psi (10.3 bar)
350 gpm (1325 L/M) @ 200 psi (13.8 bar)
250 gpm (946 L/M) @ 250 psi (17.2 bar)

